

Kameleon

Deze inbouw/en opbouwspot heeft een instelbare inbouwopening (65mm-205mm)
Uitgerust met SMD Led voor een hoge lumenoutput en gelijkmatige
lichtopbrengst.

Dit toestel wordt geleverd met een instelbare keurtemperatuur (3000/4000/5700K)

Superslanke afdekking in alu



Dimension(mm)	Ø235*16	
Cutout (mm)	Ø65-Ø205	
Watt(W)	16W	10W / 13W / 16W
Rated Input Voltage(V)	AC100-240V	AC230V
Input Voltage(V)	AC85V-265V	AC200V-240V
LED Module Input	-	
Light Source	SMD	
SDCM	<6	
CCT(K)	3000/4000/5700K	
CCT Selection DIP Switch	YES	
		1500~1650
		1500~1650
	Non-DIM	3-CCT
		1500~1800
		1500~1650
		1500~1650
CRI	≥80	
Beam Angle (°)	120°	
UGR	-	
LED Driver	Built-in	
Dimming Option	Triac	
Sensor	-	
Emergency Kits	-	
Electrical Class	Class II	
Ingress Protection (IP Rating)	IP20	
Impact Resistance (IK Rating)	-	
Product Finishing(Base)	White RAL 9016	

Materials of Optics	PS
Materials of Housing	PC/Aluminium
Lifetime (hr)	5,0000h
Glow wire test (°C)	650°C
Operating Temp. (°C)	-20°C~45°C
Storage Temp. (°C)	-20°C~65°C
Installation	Surface mount / Recessed

