



Salt

if DESIGN
AWARD
2015



>> MORE INFO



>> MORE INFO

										P	CCT	I	Flux	LOR
SALT 3	A220-03-	1 -0-	WW	WG	WR	NW	NG	NR		22W	2700K	700mA	2800 lm	79%
	A220-03-	1 -1-	WW	WG	WR	NW	NG	NR		22W	3000K	700mA	3025 lm	79%
	A220-03-	1 -2-	WW	WG	WR	NW	NG	NR		22W	4000K	700mA	3075 lm	79%
SALT 4	A220-04-	⊗ -1-	WW	WG	WR	NW	NG	NR		27W	3000K	700mA	4100 lm	79%
	A220-04-	⊗ -2-	WW	WG	WR	NW	NG	NR		27W	4000K	700mA	4175 lm	79%
SALT 5	A220-05-	⊗ -1-	WW	WG	WR	NW	NG	NR		35W	3000K	900mA	5125 lm	79%
	A220-05-	⊗ -2-	WW	WG	WR	NW	NG	NR		35W	4000K	900mA	5225 lm	79%
SALT 6	A220-06-	⊗ -1-	WW	WG	WR	NW	NG	NR		47,5W	3000K	1200mA	6550 lm	79%
	A220-06-	⊗ -2-	WW	WG	WR	NW	NG	NR		47,5W	4000K	1200mA	6650 lm	79%

220 V~ | IP20 | CRI>90 | L80B10 >60.000h



										P	CCT	I	Flux	LOR
SALT PC 3	A220-03-	1 -0-	TW	TN						22W	2700K	700mA	2800 lm	84%
	A220-03-	1 -1-	TW	TN						22W	3000K	700mA	3025 lm	84%
	A220-03-	1 -2-	TW	TN						22W	4000K	700mA	3075 lm	84%
SALT PC 4	A220-04-	⊗ -1-	TW	TN						27W	3000K	700mA	4100 lm	84%
	A220-04-	⊗ -2-	TW	TN						27W	4000K	700mA	4175 lm	84%
SALT PC 5	A220-05-	⊗ -1-	TW	TN						35W	3000K	900mA	5125 lm	84%
	A220-05-	⊗ -2-	TW	TN						35W	4000K	900mA	5225 lm	84%
SALT PC 6	A220-06-	⊗ -1-	TW	TN						47,5W	3000K	1200mA	6550 lm	84%
	A220-06-	⊗ -2-	TW	TN						47,5W	4000K	1200mA	6650 lm	84%

220 V~ | IP20 | CRI>90 | L80B10 >60.000h




⊗ *OPTIONS


2	DIM Push
4	DIM DALI

PHASE CUT PLEASE CONSULT


MAINS TRIMLESS




MAINS THICK TRIMLESS



STEEL CABLE TRIMLESS



SALT & SALT PC



OPTIONAL ACCESSORIES

WIRE TRIMLESS Accessories

FEED

Mains Trimless

A023-00-01- | W | N | NO DIM

Mains Thick Trimless

A023-00-02- | W | N | DIM



FASTENING

Steel Cable Trimless

A023-00-05- | W | N | 3 Pcs. needed



COLOUR | WW □ | WG □ | WR □ | NW □ | NG □ | NR □ | MATERIAL | AL | PMMA | RAL ⓘ >> 538

COLOUR | TW □ | TN □ | W □ | N □ | MATERIAL | AL | PC | PMMA | ⓘ >> PLEASE CONSULT



>> MORE INFO

	P	CCT	I	Flux	LOR
SALT Mini A280-00-10- WW WG WR NW NG NR	10W	2700K	700mA	1300 lm	67%
A280-00-11- WW WG WR NW NG NR	10W	3000K	700mA	1400 lm	67%
A280-00-12- WW WG WR NW NG NR	10W	4000K	700mA	1425 lm	67%

220 V~ | IP20 | CRI>90 | L80B10 >60.000h



WW



WG



WR



NW



NG



NR

OPTIONAL ACCESSORIES

WIRE TRIMLESS Accessories

FEED

Mains Trimless A023-00-01- | W | N |




FASTENING


Steel Cable Trimless A023-00-05- | W | N |




MAINS TRIMLESS



STEEL CABLE TRIMLESS



SALT MINI



COLOUR | WW | WG | WR | NW | NG | NR | MATERIAL | AL | PMMA | RAL » 538

COLOUR | W | N | COLOURS MAY AFFECT THE LIGHTING PARAMETERS » PLEASE CONSULT